

## **TECHNICAL INFORMATION**

## Series 110

Subject	Details					
Frame	Clear	Frameless				
rrame	Stand Alone	with Frame				
Vent	5/8" Direct Vent (by Dura Vent)					
Interior Design Media		Log Set with Beige Embers				
	Wood Style	Mixed Long and Short				
		Branches with Beige Embers				
	Ceramic Stones	Colors: Grey or White				
	Ceramic Stones	Size: Large or Small				
	C1 (1 (1 )	Crushed Glass				
	Glass (by others):	Pebbles				
	CINI	Leave 20% of burner and				
	General Note	grill uncovered by media				
Type of Gas	Natural Gas (NG) or Propane (LP)					
Weight	Clear 110	304 lbs., 137 kg.				
	Clear 110H	304 lbs., 137 kg.				
	Clear 110 RS/LS	381 lbs., 171 kg.				
	Clear 110 TS	381 lbs., 171 kg.				
	Clear 110 Tunnel	381 lbs., 171 kg.				
	Stand Alone 110	381 lbs., 171 kg.				
Standard		ANSI Z21.88/CSA 2.33-2014				
	Safety					
	Efficiency	ANSI P.4.1-09				
Operation	Mertik Maxitrol Remote Control (full automatic,					
Орегания	wall control unit is optional), electronic ignition					



The appliance has been certified for use with either Natural Gas (NG) or Propane Gas (LP), and NOT for use with solid fuels.

These direct vent gas fireplace heaters are sealed combustion, air-circulating gas fireplaces approved for indoor use. For indoor installation they must be installed maintaining required clearances. Refer to manual for clearance distances. Installation is recommended in living spaces such as bedrooms, living rooms, great rooms, etc. The appliance is not approved for closet installation.

The appliance must be properly connected to a venting system.

The appliance must be installed according Ortal USA requirements in addition to any local codes that may apply. If none exist then the current CSA installation code must be followed:

- USA, ANSI Z223.1/NFPA 54
- Canada, CSA B149

## **Gas Pressures & Power Output**

Models	Gas	Inlet Pressures		Manifold Pressures		Power output	
<b>Burner Series 110</b>		Min.	Max.	Min.	Max.	Min.	Max.
Clear 110/H Clear 110 RS/LS Clear 110 TS Clear 110 Tunnel Stand Alone 110	Natural Gas (NG)	7" WC 1.74	7" WC 1.74	2.1" WC 0.52	5" WC	22,800 BTU/hr	37,100 BTU/hr
	Propane (LP)	kPa	kPa	7.3"	kPa	6.68 kW 22,900	10.8 kW 28,500
		2.73 kPa	WC 2.73 kPa	WC 1.81 kPa	2.69 kPa	BTU/hr 6.72 kW	8.36 kW

## **Parts Included:**

- Ortal fireplace box
- Ceramic Glass Panel
- Choice of Ortal interior media, choose one or mix from these options:
  - o Ceramic stones (black or White Large or Small)
  - o Long and short branches with Beige embers
  - o Log set (larger logs than branches) with Beige Embers
- Ortal burner (sizes vary based on fireplace selection)
- Mertix GV60 combination control valve, Mertix Maxitrol GV60 ignition and control system (wireless remote control with battery and receiver) for LP or NG
- Spark/pilot/thermal coupling unit
- Glass removal tool (glass suction cups and 10mm ratchet wrench)
- 4 leg extensions and mounting brackets
- Full set of flue restrictor all units (not applicable for Space Creator models).
- Rutland silicon product for RS/LS/TS and Space Creator models