

TECHNICAL INFORMATION

Series 150

Subject	Details					
Evomo	Clear	Frameless				
Frame	Stand Alone	With Frame				
Vent	5/8" Direct Vent (by Dura Vent)					
Interior Design Media		Log Set with Beige Embers				
	Wood Style	Mixed Long and Short Branches with Beige Embers				
	Ceramic Stones	Colors: Grey or White				
	Ceramic Stones	Size: Large or Small				
	Class (by others):	Crushed Glass				
	Glass (by others):	Pebbles				
	General Note	Leave 20% of burner and grill uncovered by media				
Type of Cos	Natural Gas (NG) or Propane (LP)					
Type of Gas Weight	Clear 150	406 lbs., 183 kg.				
	Clear 150 H	406 lbs., 183 kg.				
	Clear 150 RS/LS					
		444 lbs., 200 kg.				
	Clear 150 TS	444 lbs., 200 kg.				
	Clear 150 Tunnel	444 lbs., 200 kg.				
	Space Creator 150	444 lbs., 200 kg.				
	Stand Alone 150	444 lbs., 200 kg.				
Standard		ANSI Z21-88-2009-CSA 2.33-				
	Safety	2009				
	Efficiency	ANSI P.4.1-09				
Operation	Mertik Maxitrol Remote Control (full automatic, wall control unit is optional), electronic ignition					



Product Specifications

The appliance has been certified for use with either Natural Gas (NG) or Propane Gas (LP), and NOT for use with solid fuels.

These direct vent gas fireplace heaters are sealed combustion, air-circulating gas fireplaces approved for indoor use. For indoor installation they must be installed maintaining required clearances. Refer to manual for clearance distances. Installation is recommended in living spaces such as bedrooms, living rooms, great rooms, etc. The appliance is not approved for closet installation.

The appliance must be properly connected to a venting system.

The appliance must be installed according Ortal USA requirements in addition to any local codes that may apply. If none exist then the current CSA installation code must be followed:

- USA, ANSI Z223.1/NFPA 54
- Canada, CSA B149

Gas Pressures & Power Output

Models Burner Sourier	Gas	Inlet Pressures		Manifold Pressures		Power output	
Burner Series 150		Min.	Max.	Min.	Max.	Min.	Max.
Clear 150/H	Natural Gas (NG)	7.0" WC	7.0" WC	0.9" WC	3.5" WC	23,300 BTU/hr	43,700 BTU/hr
Clear 150RS Clear 150LS		1.74 kPa	1.74 kPa	0.22 kPa	.87 kPa	6.83 kW	12.81 kW
Clear 150TS Clear 150 Tunnel Space Creator 150 Stand Alone 150	Propane (LP)	11.0" WC	11.0" WC	5.8" WC	10.7" WC	27,100 BTU/hr	36,900 BTU/hr
		2.73 kPa	2.73 kPa	1.44 kPa	2.66 kPa	7.95 kW	10.8 kW

Parts Included:

- Ortal fireplace box
- Ceramic Glass Panel
- Choice of Ortal interior media, choose one or mix from these options:
 - o Ceramic stones (black or White Large or Small)
 - o Long and short branches with Beige embers
 - o Log set (larger logs than branches) with Beige Embers
- Ortal burner (sizes vary based on fireplace selection)
- Mertix GV60 combination control valve, Mertix Maxitrol GV60 ignition and control system (wireless remote control with battery and receiver) for LP or NG
- Spark/pilot/thermal coupling unit
- Glass removal tool (glass suction cups and 10mm ratchet wrench)
- 4 leg extensions and mounting brackets
- Full set of flue restrictor all units (not applicable for Space Creator models).
- Rutland silicon product for RS/LS/TS and Space Creator models