

TECHNICAL INFORMATION

Series 75

Subject	Details					
T	Clear	Frameless				
Frame	Stand Alone	With Frame				
Vent	4/6" Direct Vent (by Dura Vent)					
Interior Design Media		Log Set with Beige Embers				
	Wood Style	Mixed Long and Short Branches with				
		Beige Embers				
	Ceramic Stones	Colors: Grey or White				
	Ceramic Stones	Size: Large or Small				
	Glass (by	Crushed Glass				
	others):	Pebbles				
	General Note	Leave 20% of burner and grill uncovered				
	General Note	by media				
Type of Gas	Natural Gas (NG) or Propane (LP)					
Weight	Clear 75x65	278 lbs., 125 kg.				
	Clear 75x65	278 lbs., 125 kg.				
	Tunnel Stand Alone					
	75x65 Curve	279 lbs 125 kg				
	Stand Alone	278 lbs.,125 kg.				
	75x65 Curve					
	Tunnel	278 lbs.,125 kg.				
	Space Creator 75	278 lbs., 125 kg.				
	Stand Alone 75	278 lbs., 125 kg.				
	Stand Alone 75	278 lbs., 125 kg.				
	TS	ANGLETAL 00/GG 1 2 22 221 /				
	Cofeter	ANSI Z21.88/CSA 2.33-2014				
	Safety	ANSI P.4.1-09				
Operation	Efficiency ANSI P.4.1-09 Mertik Maxitrol Remote Control (full automatic, wall control					
	unit is optional), electronic ignition					
	unit is optional), electronic ignition					



Product Specifications

The appliance has been certified for use with either Natural Gas (NG) or Propane Gas (LP), and NOT for use with solid fuels.

These direct vent gas fireplace heaters are sealed combustion, air-circulating gas fireplaces approved for indoor use. For indoor installation they must be installed maintaining required clearances. Refer to manual for clearance distances. Installation is recommended in living spaces such as bedrooms, living rooms, great rooms, etc. The appliance is not approved for closet installation.

The appliance must be properly connected to a venting system.

The appliance must be installed according Ortal USA requirements in addition to any local codes that may apply. If none exist then the current CSA installation code must be followed:

- USA, ANSI Z223.1/NFPA 54
- Canada, CSA B149

Gas Pressures & Power Output

Gas Tressares & Tower Guepar									
Models	Gas	Inlet Pressures		Manifold Pressures		Power output			
Burner Series 75		Min.	Max.	Min.	Max.	Min.	Max.		
Clear 75x65 Clear 75x65 Natural Gas	7.0" WC	7.0" WC	1.6" WC	4.7" WC	16,100 BTU/hr	29,100 BTU/hr			
Tunnel Clear 75x65	(NG)	1.74 kPa	1.74 kPa	0.39 kPa	1.17 kPa	4.73 kW	8.52 kW		
Curve Space Creator 75 Clear 75x65 Curve Tunnel Stand Alone 75/TS	Propane (LP)	11.0" WC	11.0" WC	4.5" WC	10.9" WC	13,800 BTU/hr	22,100 BTU/hr		
		2.73 kPa	2.73 kPa	1.12 kPa	2.71 kPa	4.05 kW	6.48 kW		

Parts Included:

- Ortal fireplace box
- Ceramic Glass Panel
- Choice of Ortal interior media, choose one or mix from these options:
 - o Ceramic stones (black or White Large or Small)
 - o Long and short branches with Beige embers
 - o Log set (larger logs than branches) with Beige Embers
- Ortal burner (sizes vary based on fireplace selection)
- Mertix GV60 combination control valve, Mertix Maxitrol GV60 ignition and control system (wireless remote control with battery and receiver) for LP or NG
- Spark/pilot/thermal coupling unit
- Glass removal tool (glass suction cups and 10mm ratchet wrench)
- 4 leg extensions and mounting brackets
- Full set of flue restrictor all units (not applicable for Space Creator models).
- Rutland silicon product for RS/LS/TS and Space Creator models